



SSAF BM

*For vertical glass, 7 year warranty for sloping glass. Warranty is only valid if installed by trained and qualified personnel.

Performance Data

| Technical data | 3mm single | 4/16/4 mm double |
|---|------------|------------------|
| Solar Energy Transmission, T_e | 50% | |
| Solar Energy Reflection, P_e | 13% | |
| Solar Energy Absorption, a_e | 37% | |
| Visible Light Transmission, T_v | 36% | |
| Visible Light Reflection (External), P_{ve} | 11% | |
| Visible Light Reflection (Internal), P_{vi} | 11% | |
| Ultraviolet Transmission, T_{uv} | 1% | |
| g value | 0.71 | |
| Shading Coefficient | 0.7 | |
| Total Solar Energy Rejected | 39% | 36% |
| Glare Reduction | 59% | |
| U value, single glazing ($W/m^2.K$) | 5.62 | |
| Film Colour / appearance | Bronze | |
| Installation position | Internal | |

Viewed from outside

Features and Benefits

- Bronze Translucent Matte Film.
- Transmits 50% of visible light yet maintains privacy, 'light-through without see-through.'
- Shatter resistant, 2mil thickness, reduces danger of flying, broken glass.
- Pleasing alternative to plain glazed partitions in office or factory.

