



# SSAF CLUV SR

\*For vertical glass, 7 year warranty for sloping glass. Warranty is only valid if installed by trained and qualified personnel.

## Performance Data

Technical data	t3mm single	4/16/4 mm double
Solar Energy Transmission, $T_e$	84%	
Solar Energy Reflection, $P_e$	9%	
Solar Energy Absorption, $a_e$	7%	
Visible Light Transmission, $T_v$	90%	
Visible Light Reflection (External), $P_{ve}$	9%	
Visible Light Reflection (Internal), $P_{vi}$	9%	
Ultraviolet Transmission, $T_{uv}$	0.5%	
g value	0.85	
Shading Coefficient	0.9	
Total Solar Energy Rejected	14%	15%
Glare Reduction	13%	
U value, single glazing ( $W/m^2.K$ )	-	
U value, double glazing, Air filled ( $W/m^2.K$ )		-
Film Colour / appearance	Clear	
Installation position	Internal	

Viewed from outside

## Features and Benefits

- Very high UV filter to give best possible fade reduction from a clear film.
- Additional UV 'absorbers' within the adhesive for extra protection.
- SSAF Films are protected by a patented scratch-resistant coating.
- Excellent film to help alleviate medical conditions caused, or aggravated by U.V. light.
- Excellent film to help protect valuable interior furnishings and fabrics from fading.
- Excellent film to help protect the contents of museums galleries from the harmful effects of Ultra Violet light.

